

## TOYO SUBMERSIBLE MIXER

# TA

### FEATURE

- Additional equipment for pumping up materials by slurry pump. Suitable for expand the area of agitation.
- One to four units of TA can be used as attachment to a pump or individually. Models of 2.2kW to 7.5kW are available.
- Special band for installation makes the angle of attachment easily.



OUTPUT	2.2~7.5kw
--------	-----------

### SPECIFICATION

MODEL	OUTPUT (kW)	POLE (P)	VOLTAGE (V)	STARTING	WEIGHT (kg)	CABTYRE CABLE LENGTH: 10m (Symbol x mm <sup>2</sup> x core)
TA-3(L·R)	2.2	4	200	DIRECT ON LINE	90	3PNCT×5.5 <sup>#</sup> ×4C
TA-5(L·R)	3.7	4	200	DIRECT ON LINE	100	3PNCT×5.5 <sup>#</sup> ×4C
TA-7.5(L·R)	5.5	4	200	DIRECT ON LINE	120	3PNCT×5.5 <sup>#</sup> ×4C
TA-10(L·R)	7.5	4	200	DIRECT ON LINE	140	3PNCT×8 <sup>#</sup> ×4C

- Specifications are changeable without notice. Please ask for Specification Sheet for the details.
- R type: clockwise rotation / L type: counter clockwise rotation seeing from the bottom of equipment. Standard equipment is L type.

### SIZE

Unit : mm

MODEL	A	B	C
TA-3	671	275	565
TA-5	755	275	615
TA-7.5	773	300	620
TA-10	813	300	660

- Specifications are changeable without notice. Please ask for Specification Sheet for the details.

